

P-430 NAT

2-MIL PTFE FILM TAPE

PRODUCT DESCRIPTION

P-430 NAT has an aggressive solvent resistant acrylic adhesive that offers superior adhesion to most surfaces. P-430 NAT is ideal for use in aerospace and electrical applications.

FEATURES

- Resistant to Freon and many other chemicals such as fuels and solvents.
- Easy to dispense and unwind makes the P-430 tape easy to handle.
- Shows superior adhesion even on damp or wet surfaces.
- Can be removed easily leaving no adhesive residue.
- Prevents abrasion, squeaking or wearing on materials such as metallic's, ceramics, metals or plastics.
- Provides outstanding conformability when used on curved or irregular surfaces

PRODUCT CONSTRUCTION

PTFE FILM
ACRYLIC ADHESIVE

APPLICATION

- Highly versatile PTFE tape engineered primarily for anti-friction masking, flashing, release and separator applications.
- Used where ever a slick surface is required, speeding up the movements of materials and or reducing equipment wear.
- Ideal as a liner for chutes and rails preventing powder build up; parts or package jam ups.
- High temperature release film used on heat sealer or aerospace flashing applications.
- Used for hanger wrapping to help products through paint or coating solutions.
- Can be used to help prevent electrolytic corrosion of different materials.

PROPERTIES, CERTIFICATIONS AND SPECIFICATIONS

Backing Material	PTFE Film	
Adhesive	Acrylic	
Color	Gray	
	Imperial	Metric
Total Tape Thickness	3.6 mil	0.091 mm
Tensile Strength	27 lbs/in.	47.7 N/10mm
Elongation	120%	120%
Adhesion to Steel	36 oz/in	4.0 N/10mm
Dielectric Strength	12,000 volts	12.0 kV
Insulation Class CSA	311°F	155°C
Insulation Class UL	311°F	155°C
Certifications	UL-510 & CSA C-22-2	
Government Specification	ASTM E595	

*CAUTION: The above are typical values and should not be used in writing specifications. Customer is responsible to ensure product meets intended application requirements before approved for use.

GENERAL STORAGE CONDITIONS

Best stored between 50°F-80°F / 10°C-27°C, 25-50% relative humidity; out of direct sunlight.

PRECAUTION REMINDER

Surface should be clean, free of oil, moisture and dirt before applying. Pressure-sensitive adhesive tapes may require pressure by roller, hand or press when applying. Not doing so may affect the general properties and appearance. Please inspect your surface prior to application; this tape may not adhere well to extremely uneven or distorted surfaces. Please remember to allow adequate time for full adhesive strength.

WARRANTY INFORMATION

The following is made in lieu of all warranties, expressed or implied, including the warranty of merchantability and fitness for a particular or ordinary purpose. NITTO DENKO AMERICA warrants that its products meet the applicable specifications at the time of shipment from our warehouse and NITTO DENKO AMERICA's sole obligation shall be to replace any such quantity of the product which fails to meet NITTO DENKO AMERICA's specifications or to issue a credit for such merchandise for a period of six (6) months from the date of shipment.

NITTO DENKO AMERICA MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

NITTO DENKO AMERICA shall not be liable for any injury, loss or damage, direct or consequential, arising out of or in connection with the use or the inability to use the product, nor shall any recovery of any kind in total against NITTO DENKO AMERICA be greater in amount than the purchased price of the specific material sold causing the alleged loss, damage or injury. Before using, buyer shall be responsible to determine the suitability of the product for his intended use, and buyer assumes all risk and liability in connection therewith. The foregoing may not be altered except by an agreement signed by an officer of NITTO DENKO AMERICA.

Any delays in or failure by either party hereto in the performance of any obligations hereunder shall be excused if and to the extent caused by occurrences beyond such party's reasonable control, including Acts of God, strikes or other labor disturbances, war, whether declared or not, fire, inability to secure transportation or any other cause or causes which cannot be reasonably controlled by such party.