QED

Quick dry electrical & workshop degreaser







QED aerosol is a very fast evaporating low odour solvent degreaser, which dries rapidly to a residue free finish. QED incorporates an advanced 360° valve system which allows the product to be sprayed even when inverted, for added convenience and access to components which are difficult to reach.

ADVANTAGES

Removes oil, grease and particles from metals machinery and electrical components, drying rapidly to a residue free finish

Fast evaporation and zero residue makes QED an exceptional brake and clutch cleaner

Refined formulation will not damage sensitive equipment or components

Contains no aromatic hydrocarbons

Ideally suited for all manufacturing and maintenance environments

Low odour

360° spray action

Incorporates pbca technology (compressed air propellant) helping to reduce your environmental impact

TYPICAL APPLICATIONS

- → Removal of oil and grease deposits from machinery and components for routine inspection and maintenance
- Cleaning components prior to painting or bonding
- Flushing oil and particulates from brake/clutch mechanisms, motors and alternators
- May be used for cleaning and degreasing electrical and electronic assemblies including motors, solenoids and switchgears
- Removal of temporary protective coatings from components prior to assembly

APPLICATION INSTRUCTIONS

- 1. Spray QED onto the surface to flush away debris.
- 2. Wipe away excess dirt and grease residues.
- 3. Re-apply where required.
- 4. Wipe away excess QED or allow to air dry.

NOTE: Ensure electrical equipment is switched off and cool prior to application. Ensure that the product has dried fully before reconnection.



TECHNICAL DATA

APPEARANCE	Aerosol
ODOUR	Mild solvent odour
SOLUBILITY	Insoluble in water
PROPELLANT	Hydrocarbon
FLASH POINT (°C)	-4°C (closed cup)
VOC CONTENT	640g/l
PACK SIZE	400ml Aerosols

PRECAUTIONS

Keep away from heat, sparks and open flame. Use in a well-ventilated area. Avoid inhalation of vapour.

STORAGE PRECAUTIONS

Store at moderate temperatures in a dry well ventilated area. Keep between 0 and 40°C .

HEALTH AND SAFETY

Health and Safety Data sheet available separately.

RELATED PRODUCTS



FASTKLEANPowerful fast drying degreaser



SUPERSOLVE ASElectronic cleaner for critical surfaces



LOTOXANE® FAST
A faster drying Lotoxane® variant
which evaporates three times faster
than standard Lotoxane®



LOTOXANE®Safe high flash point degreaser



ISO 14001:2004 Cert No. 1263



150 9001:2008 Quality Management Q 05320











