

KLETTOPLAST® - Hook

Item no. 63144
KLETTOPLAST® - Hook
Engaging elements:

10 rows, double hooks

Material:

Polyamide

Thickness:

approx. 2,0 mm

Construction:

extruded

Standard widths:

approx. 25 mm

Weight:

approx. 12,0 g/m

Colours:

black




Temperature range:

approx. - 30°C to + 100°C

Make-up:

50 m-rolls, other make-up on request

Fastener combination

with Fastener Item no. thickness* (mm) Fastening efficiency			Peel strength 		Shear strength 		Tensile strength 	
			Average value (N/cm)	Min.value (N/cm)	Average value (N/cm²)	Min.value (N/cm²)	Average value (N/cm²)	Min.value (N/cm²)
53248	3,0-4,0	Original	approx. 5,0	2,5	approx. 30,0	15,0	approx. 15,0	7,5

* Fastener thickness without adhesive

Fastener thickness:

A fastener closed acc. to DIN 3415 part 2, para 5.2.1, measured with a microscanner with 30 mm disc diameter at a closing pressure of $0,14 \pm 0,04 \text{ N/cm}^2$ according to DIN 53.370

Fastening efficiency:

Testing of the peel and shear according to DIN 3415 part 2, para 5.2 and 5.3.
Testing of the tensile according to CEN TC 248/WG5 N 30, issue 1/92.

All information in this document has been compiled carefully from the best knowledge gained by Gottlieb Binder GmbH & Co.KG from the framework of their quality management systems. It describes product from the aspect of composition and application but does not constitute any quality assurance. Besides it does not release the customer from their obligation to control received goods and to carry out initial product testing nor provide any justification for the pursuit of third party claims. In the legal sense, no quality safeguard is implied or given. The right is reserved to make technical alterations.