

## XIAMETER® AFE-0400 Antifoam Emulsion

#### Water based 10% active textile emulsion

#### **FEATURES**

- Immediate foam knockdown
- Long term foam inhibition
- Low addition levels Rapid dispersion in aqueous foaming systems
- Stable in textile processes at pH 4-11
- Foam control up to 100°C
- Good compatibility with dye stuffs, surfactants and textile auxiliaries

#### **APPLICATIONS**

 XIAMETER® AFE-0400 Antifoam Emulsion controls foam in the following processes:
 Dyeing, printing, fabric sinking, latex coating, bleaching, scouring, finishing and sizing.

#### **TYPICAL PROPERTIES**

Specification Writers: These values are not intended for use in preparing specifications. Please contact your local XIAMETER<sup>®</sup> sales representative prior to writing specifications on this product.

| Test               | Unit  | Value              |
|--------------------|-------|--------------------|
| Chemical nature    |       | Silicone emulsion  |
| Appearance         |       | Off white pourable |
|                    |       | emulsion           |
| Active ingredients | % w/w | 10                 |
| Viscosity at 25°C  | cPs   | 500-2000           |
| pH                 |       | 5.0-7.0            |
| Emulsifier type    |       | Non-ionic          |
| Suggested starting | ppm   | 50-100             |
| concentration      | - •   |                    |
| Diluent            |       | Water              |

#### **HOW TO USE**

For optimum efficiency, XIAMETER AFE-0400 Antifoam Emulsion should be diluted with cold soft or distilled water in the ratio of 1 part XIAMETER AFE-0400 Antifoam Emulsion to 9 parts water (maximum). The diluted emulsion may require gentle stirring before use if stored for more than 24 hours.

#### **BENEFITS**

The emulsion system has been carefully designed for optimum stability, especially in hot aqueous textile liquors, to minimize the risk of siloxane deposition and oil spotting. Good compatibility with dye bath components ensure trouble free processing.

# PRODUCT SAFETY INFORMATION

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT **INCLUDED IN THIS** DOCUMENT. BEFORE HANDLING, READ PRODUCT AND MATERIAL SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL, **ENVIRONMENTAL, AND HEALTH HAZARD** INFORMATION. THE MATERIAL SAFETY DATA SHEET IS AVAILABLE ON THE XIAMETER WEB SITE AT WWW.XIAMETER.COM.

#### **STORAGE**

Product should be stored between 0°C and 40°C in original, unopened containers. The most up-to-date shelf life information can be found on the XIAMETER Web site in the Product Detail page under Sales Specification.

#### **LIMITATIONS**

This product is neither tested nor represented as suitable for medical or pharmaceutical uses. Not intended for human injection. Not intended for food use.

### LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

DOW CORNING
SPECIFICALLY DISCLAIMS
ANY OTHER EXPRESS OR
IMPLIED WARRANTY OF
FITNESS FOR A
PARTICULAR PURPOSE OR
MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.